Miscellaneous Valves - Series Sight Glass

Screwed Double Window Sight Glass



Main Features :-
CF8M 316 construction
PTFE Glass Seals
Swinging Flap to indicate flow
-20 / + 200C 10 bar rated
1/2" to 2"
BSP Female ends
3.1 certs available



Additional Technical Specification:-

MATERIALS LIST:

NO.	PART NAME	MATERIAL
1	BODY	CF8M
2	CAP	CF8M
3	GASKET	PTFE
4	STEM	SUS316
5	GLASS PARCEL	GLASS
6	INDICATOR	CF8M


DIMENSIONS:


SIZE		4	44	ī. ī	
DN	NPS	d	d1	L	Н
15	1/2"	15	38	112	68
20	3/4"	20	38	112	68
25	1"	25	38	112	68
32	11/4"	32	45	145	110
40	11/2"	40	45	145	110
50	2"	50	55	168	131

FEATURES:

- PIPE THREAD IN ACCORDANCE:NPT,BSPT, DIN259,DIN2999,ISO 228 CLASS A
- INVESTMENT CASTING BODY
- MATERIAL:

SUS316/ASTM A351Gr-CF8M/DIN1.4408





ISO 9001:2015 Accredited Company

Tel: +44(0)1386 552369 Fax: +44(0)1386 554227 sales@allvalves.co.uk www.allvalves.co.uk