

Main Features :-

Full bore ball valve	Available with single acting
PVC valves	Double acting actuator
FIP/GF option in ABS, CPVC, PP	Switchbox
EPDM or FPM (Viton) Seals	Solenoid
Imperial or Metric plain ends	Electro pneumatic positioner
1/2" to 4"	Assembled and Tested
BSP female ends option	8 bar rated



TYPE: 942P PNEUMATIC

Technical Specifications and Key Dimensions:

Specifications:	
Actuator housing:	Hard anodised aluminium
Actuator ATEX rating:	ATEX II 2GD EExd
Actuator Temp rating:	-20 +80C
Actuator pressure rating:	8 bar Max
Valve Approval:	FIP valves made of WRAS materials
Valve ends available:	Plain end, BSP or flanged
Size range:	1/2" to 4"
Valve temp limits:	-10 to +100C
Valve pressure limits:	40 bar at ambient temperature


Assembly Overview:-

A cost effective pneumatically operated brass ball valve available in double acting (air to open air to close) or single acting (failsafe, air to open spring to close). Our main range is Hidroten PVC ball valves but we also offer FIP and GF.

Don't forget your Switchboxes and / or Solenoid valve accessories.



Brands in the AllPlastics™ Range:



*Don't forget we offer pipe and fittings



	Double Acting		Single Acting	
Size	F	H	F	H
1/2"	86	174	86	174
3/4"	94	182	94	182
1"	122	210	122	122
1 1/4"	131	219	131	131
1 1/2"	150	238	150	150
2"	177	265	177	278

AllPlastics™ primary offering is Hidroten for 2 way and 2 way and 3 way valves. Above dimensions based on Hidroten

ISO 9001:2015 Accredited Company

Tel: +44(0)1386 552369 Fax: +44(0)1386 554227 sales@allvalves.co.uk www.allvalves.co.uk

Allvalves Online Ltd, Automation House, Unit 2, Pershore, WR10 2DF UK

*Please note that all datasheet are generally generic and are subject to change without prior notice. They are for reference only.