Gate Valves

Main Features: -

- Screwed BSPP
- Bronze Body & Bonnet
- Cast Handwheel
- Rated PN20
- Temperature -20°C to 180°C

*Temperature and pressure determined by valve body, seat etc.

Suitable Applications & Approvals:



VALVE DI MENSI ONS



SERIES: 30063

MANUFACTURER:



No	Name	Materials
1	Nut & Washer	Mild Steel
2	Name Plate	Aluminium
3	Handwheel	Cast Iron
4	Stem	Brass
5	Gland Nut	Bronze
6	Gland Packing	PTFE
7	Bonnet	Bronze
8	Check Nut	Bronze
9	Wedge	Bronze
10	Body	Bronze

Size	В	Н	W	Kg	Cv	Kv
1/4"	44	77	54	0.31	-	-
3/8"	44	77	54	0.31	-	-
1/2"	46	77	54	031	16.4	14
3/4"	50	85	54	0.5	37.4	32
1"	55	102	65	0.54	66.7	57
1 1/4"	61	115	65	0.7	105.3	90
1 1/2"	63	126	76	1.03	150.9	129
2"	71	158	82	1.2	269.1	230
2 1/2"	88	189	100	2.6	500.8	428
3″	99	226	115	3.9	795.6	680
4"	118	265	135	6.5	1273	1088

Н (10)

Cv—Flow rate in US GPM at a pressure drop of 1 PSI

Kv—Flow rate in m3 per hour at a pressure drop of 1 bar

Pressure Equipment Directive Category

1/2" to 1" 1 1/4" to 2" 2 1/2" to 3" SEP CAT1 (CE) CAT2 (CE) CAT1 (CE)









